

teleskopy.pl



Laser rangefinder Leica Disto D3 High-performance Leica Disto D3 laser range finder with high precision of 1 millimeter, with Power Range technology allowing measurements up to 100 meters, with angle angle measurements up to 45 °, the smallest on the market . Characteristics

- Quick and accurate distance measurements
- The smallest rangefinder in the world
- Power Range Technology - long target measurements (80 m) without target sight
- The built-in tilt sensor quickly and easily determines tilt up to 45 °. The tilt sensor calculates the actual horizontal distance, so reliable measurements are guaranteed
- Aim the laser beam directly on the target, no matter if you measure from behind a corner, through holes or from the edge: thanks to the foot, you are prepared for any situation during measurements. The instrument automatically detects the spread foot, which avoids the additional costs associated with erroneous measurements
- DISTO D3 can calculate surfaces, volumes, room sizes and various variants of the Pythagorean functions. The measurement trigger and memory for up to 20 measurements complement the long list of instrument functions cleverly designed to facilitate your work
- Built-in tilt sensor provides horizontal distance

measurement

- The sensor assesses the lighting conditions and automatically switches on the keypad and display lights
- The horizontal distance can be measured without any problems despite the obstacles on the aiming line
- Reliable measurements from edges and corners
- Values such as the total wall length, wall and ceiling surfaces can be obtained by pressing the button
- Accurate calculation of room angle with only three measurements

Technical parameters

- Effective range: 0.05 m (5 cm) - 80 m without target sight, 100 m with sciming disc (shield included with the rangefinder)
- Accuracy: +/- 1 millimeter
- Min / max measurement: YES
- Continuous measurement mode: YES
- Addition and subtraction of measurements: YES
- Area and volume measurements: YES
- Slope measurements: YES, up to 45 ° accuracy 0.001%
- Indirect measurements using the Pythagoras function: YES
- Memory of last measurements: YES, 20
- Auto timer: YES
- Backlight of the screen: YES
- Immunity class: IP 54
- Power supply: 2 x AAA battery ("small finger"), up to 5000 measurements on one set of batteries
- Dimensions [mm]: 125 x 45 x 24

Equipment included

- laser rangefinder
- carrying case
- 2 x AAA batteries
- target plate
- belt

user manual

- manufacturer's certificate
- Warranty 2 years
- Additional product photos