

teleskopy.pl



Dipol D212 SL PRO with 6x magnification is a prized 1+ generation night vision binoculars with good optoelectronic parameters and a robust design. One of the favorite night vision binoculars among the hunters. In conjunction with an additional laser display (see below) it is an ideal set to look in total darkness for even small targets over long distances. Especially appreciated by hunters and trainers, it is ideal for moonless, traditionally unserviceable nights. Included is a powerful laser illuminator that greatly increases the range of the device (up to 500 - 600 meters) Technical parameters of the night vision device

- Generation: 1+
- IR illuminator: built-in, diode (also available laser light, optional)
- Control: analog
- Zoom: 6x
- Resolution: 40 lines / mm
- Detection range: 300 m
- Range of recognition: 150 m (detection of wild boar at moonlight)
- Field of view: 12 °
- Focal length of the lens: F = 120 mm
- Focus range (Diopter): +/- 4
- Adjustment range of the eye track: 59 - 70 mm
- Focus range: from 10 m to infinity
- Power supply: two 3V Li-Fe batteries (included)
- Temperature range: from -40 to + 40 ° C
- Working time without changing the power

source: up to 120 hours (30 hours with switched on IR LED) â€¢ Dimensions: 270 x 127 x 65 mm â€¢ Weight: 1120 g
Technical parameters of the LR-3 laser display â€¢ Power: 100 mW â€¢ Type: laser â€¢ Length of the light wave: 810 nm
â€¢ Focus of the bundle: 0.1 ° - 5 ° â€¢ Power supply: 1 x AA ("finger") (included) â€¢ Temperature range: from -40 to + 40
â€¢ Working time without changing the power source: 6 hours â€¢ Dimensions: 114 x 24 x 31 mm â€¢ Weight: 80 g Usage
forestry hunting sailing nature fishing Additional information DURABLE AND LIGHTWEIGHT ALUMINUM ALLOY
BODY PROVIDES HIGH STRUCTURE RESISTANCE, AND THE ADDITIONAL GUM COVER MAKES THAT THE
LIGHTBOOK IS CLEARLY IN HANDS COMFORTABLE LOCKED CONTROL BUTTONS ALLOW THE FAST ON AND
OFF THE BICYCLE AND THE BUILT-IN BATHLIGHT DIODES ON THE CASE, INDICATE CURRENT DEVICE MODE
(ON / OFF, IR LED ON / OFF) THE PARTITION LOCATED ON THE BODY IS LIGHTED IN THE CASE OF
EXCEEDING THE LIMIT LIGHT, CHRONIC SO THE ELECTRONIC FROM THE NECTAR BEFORE DAMAGE A
BUILT-IN LED DISTRIBUTION ENABLES CONDUCTING OBSERVATIONS EVEN IN FULL DARK CONDITIONS;
ILLUMINATOR HAS A REGULATION OF KTA VISKA CENTER ON THE BIKE BOX ADJUSTMENTS A RAIL FOR
FIXING AN OPTIONAL LASER LIGHT IS FINISHED Warranty 12 months for the transducer, 24 months for other
elements >> FREQUENTLY ASKED QUESTIONS << Question : What is the difference between the 1 and 2
generation night vision devices? I want to buy a night vision device, but I would like to learn more about night vision
technology. Answer: Basic information can be found in the HOW TO OPERATE THE NECTOR (click to read)