

teleskopy.pl



Robust roof binoculars in an area with classic natural parameters 10x42. Good coatings on all elements of the optics are a guarantee of the depth of reproduction and brightness of the images obtained. High resistance to weather conditions (O-rings and nitrogen filling) and resistance to mechanical damage (rubberizing) ensure the longevity of the binoculars. This is a very interesting proposition for beginners and intermediate admirers of bird and nature observation.

Includes a neck strap, lenses covers and glasses, and a carrying case with a belt

Technical parameters

- â€¢ Lens diameter: 42 mm
- â€¢ Zoom: 10x
- â€¢ Exit pupil: 4.2 mm
- â€¢ Construction of prisms: roof
- â€¢ Optical system: 8 elements groups
- â€¢ Material of glass elements: Optical glass Bak-4
- â€¢ Field of view: 119 m / 1000 m
- â€¢ Retracting the output pupil: 15 mm
- â€¢ Minimum distance of observation: 2 m
- â€¢ Twilight factor : 20
- â€¢ Adjusting for eye defect: +/- 4 D
- â€¢ scope of adjustment of the spacing of pupils: 55 - 73 mm
- â€¢ Eyecups: adjustable, twist-up type
- â€¢ Waterproof: yes, up to 1 m to 30 minutes
- â€¢ Anti-reflective layers: FMC (Fully Multi-Coated), PhC (Phase Coating - phase coatings on prisms)
- â€¢ Weight: 710 g

Usage astronomy hunting planes nature scenery Warranty 5 years