

# teleskopy.pl



The ability to accurately measure distances at the touch of a button gives you a significant advantage in the field when you need to make a quick decision. Regardless of weather and landscape, the Nikon PROSTAFF 3i is the perfect companion in every situation. A new laser rangefinder containing the latest technical solutions in a compact, lightweight and durable body. The system of switching the priorities of objects displays the distance to the nearest object - even if there is an overlapping background - or the farthest object, which is useful in a wooded area. By holding the power button for about 8 seconds, you can accurately measure the distance for moving targets. Characteristics

- measurement range: 7.3-590 m
- easy switching between distance reduced to level and real distance
- ID technology (slope up / down slope)
- the accuracy of the distance display is 0.1 m
- high quality 6x magnification monocular with multilayer coatings for a clear, clear image.
- large eyepiece for comfortable aiming (18 mm)
- wide field of view (7.5 degrees)
- a large offset of the exit pupil facilitates the observation of people wearing glasses
- diopter adjustment function
- single or continuous measurement (up to 8 seconds)
- resistance to rain - equivalent to class 4 (IPX4) JIS / IEC resistance (under Nikon test conditions)
- Possibility of working in a wide temperature range: -10 ° C to + 50 ° C

Technical parameters

- measurement range: 7.3-590 m
- magnification: 6x
- effective lens diameter: 21 mm
- field of view: 7.5°
- exit pupil diameter: 3.5 mm
- distance of the exit pupil: 18.3 mm
- measurement modes: real distance and

---

reduced to the level â€¢ distance display (accuracy): 0.1 m â€¢ distance measurement priorities: distance priority of the first and second plan â€¢ continuous mode yes, up to 8 sec. â€¢ automatic shutdown: yes, after 8 seconds of inactivity â€¢ power supply: CR2x1 â€¢ dimensions: 112 x 70 x 36 mm â€¢ weight (without batteries): 160 g â€¢ operating temperature range: -10 ° C to 50 ° C â€¢ watertightness and anti-fog protection: yes Warranty 1 year