

# teleskopy.pl



Universal charger designed for charging two lithium-ion batteries type 18650, 18500 or AA (14500). It has two independent DC charging channels. The charger is equipped with reverse polarity protection, so there is no risk of damage to the battery or charger if the batteries are inserted backwards. The charger has a plug for 230 V mains and for a cigarette lighter. ATTENTION: Do not put the battery in a non-polarity condition for a long time. The device is easy to use. Simply connect the charger to the mains and insert the batteries. Charging will start automatically. LEDs, two colors, determine the charging status. Each of them refers to a separate battery. Technical data ∅ input voltage: AC 100V - 240V ~ 50Hz / 60Hz / DC 12V-24V 0.6A Max ∅ AC voltage at the output: 4.2 V ± 0.05 V ∅ output current intensity: 500 mA x 2 CH ∅ range: 450 mA - 600 mA (CV = 3.7V) ∅ charging current range: 2.50 V-4.25 V x 2 CH ∅ operating temperature: 0- + 35 ° C ∅ operating humidity: ∅90% ∅ storage temperature: -20 ° C to + 80 ° C ∅ storage humidity: RH: ∅85% ∅ atmospheric pressure: 70 - 106 Kpa ∅ length: 135 mm ∅ width: 60 mm ∅ height: 30 mm ∅ weight: 108 g