

teleskopy.pl



MONARCH 7 IL is Nikon's peak achievement in the field of weapon scopes. The image in the field of vision is distinguished by brightness and high contrast. Lenses with multilayer anti-reflective coatings ensure maximum transmission of light. The picture is not only clear and crystal clear, but also well balanced color. Glass-threaded cross-stitch and a robust, one-piece tube with a diameter of 30 mm ensure high durability. Eyepiece with fast focusing is characterized by a large offset of the exit pupil, which allows accurate aiming in the entire zoom range. Adjusting the wind and height correction with the immediate reset function. The cross-hair highlighting can be adjusted in the range of 32 degrees of brightness. Characteristics

- 30 mm tube diameter and 4x zoom
- a light point with a wide intensity range, with automatic shut-off
- Lenses with multilayer anti-reflective coatings
- a large diameter eyepiece with convenient removal of the exit pupil
- manual correction of the wind and height correction with the immediate zeroing function enabling easy and accurate adjustment of the cross thread
- lightweight and robust one-piece main body
- etched cross of threads for greater durability
- eyepiece with quick focusing of the thread cross
- waterproof construction protected against fogging, ensuring the correct operation of the telescope in various conditions
- the eyepiece cover can be used to open the battery cover

Technical parameters

- model: Nikon Monarch 7 IL 1.5-6x42 BRA15001
- magnification (x): 1.5-6
- Lens diameter: 42 mm
- coatings: multilayer
- cross: made of threads, R # etched
- Excavation: 7 mm (with 6x magnification)
- distance between output tube: 96.5 - 94 mm
- tube: $\varnothing = 30$ mm, one-piece
- Lens diameter: 49.3 mm
- external eyepiece diameter: 44 mm
- immediate resetting of the knob: yes
- adjustment (mm / 1 click) @ 100 m: 7
- regulation (MOA / 1 click): 1/4
- maximum internal cross thread adjustment (MOA): 156
- parallax regulation: from 91.44 m to infinity
- field of view: 15 ° - 3.8 ° / 26.4 - 6.6 m / 100 m
- backlight: yes, 32 degrees of intensity
- automatic power off: yes, two hours after the last press of the control button
- power supply: CR2032x1
- watertightness and protection against evaporation (nitrogen): yes
- in the set of lids, sun visor
- length: 311 mm
- weight: 590 g
- Warranty 30 years