

# teleskopy.pl



Delta Optical Titanium HD riflescopes are the latest addition to the Titanium spotting scope. The new HD optics, thanks to which the new telescopes reach a very large field of view, ensuring a free field view. In addition, the so-called "tube effect", and the large eyepiece lens provides very comfortable observation. The new Titanium HD series includes viewfinders with the following parameters: 2,5-10x56 2.5-10x56 with parallax regulation (SF) 2.5-10x56 with digital backlight (Di) 2.5-15x56 with extended, 6x zoom The Delta Optical Titanium spotting scope is designed for those who do not accept compromises. High transmission of light, for a single layer of 98% and for the entire telescope, 92% put them among the best. A centrally illuminated red dot will help you track down the target even in the conditions of a special lighting. Another characteristic feature of the Delta Optical Titanium spotting scope is high mechanical resistance. Built from a tube with a diameter of 30 mm, they withstand arrows even on weapons with a strong caliber 9.3 x 62! Thanks to nitrogen filling, they are also water and fogproof. Titanium telescopes are of exceptional quality at a reasonable price. Riflescope intended for weapons with kinetic energy up to 6500 J. Technical parameters: 200

magnification: 2.5-10x    Lens diameter: 56 mm    Reticle: German 4A, in the second plan    parallax adjustment knob  
backlight: central point, 11-step adjustment    daylight-night lighting with a large brightness span    Center point  
diameter @ 100 m: 11.4 mm @ 10x    field of view per 100 m: 14.4 m @ 2.5x - 3.7 m @ 10x    Angular field of view:  
8.22 ° @ 2.5x - 2.12 ° @ 10x    cross adjustment (1 click): 1/4 MOA    total adjustment range: 50 MOA    the ability to  
zero the target drums    distance from the eye: 99 - 98 mm    Output pupil diameter: 11.6 mm @ 2.5x - 5.6 mm @ 10x  
twilight efficiency: 11.83 @ 2.5x - 23.66 @ 10x    light transmission of 93% ( $\lambda = 550$  nm)    coatings on lenses:  
multiple (Fully Multi Coated)    water resistance: 0.3 kg / cm<sup>2</sup>    filling gas: nitrogen    body material: aluminum 70%,  
brass 20%, steel 10%    tube: one-piece 30 mm    length: 370 mm    weight: 772 g    shock resistance: 1000 G / 65  
J    functional temperature range: -20 ° C to + 71 ° C    Warranty 10 years