

teleskopy.pl



The Bushnell H2O line is a completely waterproof binoculars, whose housings are covered with a Soft Texture Grip rubber armor, guaranteeing a great grip and protection against knocks and falls from a low height. A proposal for lovers of water sports and all other users who want to use binoculars in all conditions, without fear of wetting, dusting or fogging up the interior. Convenient and fast focusing is carried out with a central knob. In addition, each H2O binocular has adjustable eyecups and dioptric regulation on the right eyepiece for leveling any differences between the left and right eye of the observer. Bushnell H2O 12x25 Roof Binoculars are a compact version with 12x magnification and 25mm objectives. Day-to-day binoculars offering a wide field of view and a bright image with almost pocket-sized dimensions and low weight. Thanks to the prisms in the Roof (roof) system, the binoculars are compact and easily fit into a small bag or even in a larger pocket. The robust gumming of the housing absorbs random impacts, and its ergonomic profile and non-slip texture provides a secure, comfortable grip. Technologies used

- MultiCoated: the most important glass-air boundaries have been repeatedly coated with anti-reflective coatings, thanks to which the unwanted reflection and the loss of light passing through the optical system have been reduced.
- BaK-4: high-quality optical glass from which prisms were used in binoculars. BaK-4 glass prisms offer brightness and clarity of the image at a level unattainable for binoculars using Bek-7 cheaper optical glass.
- Water Proof: the binoculars' tubes have been filled with dry nitrogen and sealed with O-rings, which prevents the optics from internal fogging, and makes binoculars resistant to rain, dust and temporary immersion.
- Soft Texture Grip: rubber armor with a soft non-slip texture that provides a firm grip even wet or frozen hands and cushioning impacts and falls from a low height. Includes cover and neck strap.

Technical data

- magnification: 12x
- Lens diameter: 25 mm
- Blow diameter: 2.1 mm
- eye: 12 mm
- minimum observation distance: 4.6 m
- field of view: 6.5 ° / 114 m / 1000 m
- prism system: roof (Roof)
- optical glass: BaK-4
- coatings: Multi Coated
- weight: 280 g
- producer: Bushnell, USA