

teleskopy.pl



Fenix ~~â€¢â€¢~~CL30R is more than just a camping flashlight, it's the source of light, where you will spend unforgettable moments with friends and family. The torch was designed in the form of a lantern, which will illuminate the space approximately 35 meters on average with the power of up to 650 lumens. The CL30R flashlight has been equipped with a micro USB socket, through which we can charge 18650 batteries in the middle of the flashlight. It is worth noting that the CL30R has been prepared to work on three, two or one power cell. All batteries are supervised by 4 green LEDs indicating the level of charge of the batteries. The battery chamber provides protection against cold. If you are going to the campsite even on the coldest days of the year, the CL30R flashlight batteries will not self-discharge. The standard USB socket, which was placed next to the micro USB input, is used to connect devices that require charging, for example a phone, tablet or a smaller flashlight. It is the power bank function that makes the Fenix ~~â€¢â€¢~~CL30R a unique device that will work perfectly well both as a flashlight and as an additional power source. This functionality proves extremely useful on long trips to places where we do not have access to the network current. The Fenix ~~â€¢â€¢~~CL30R tourist flashlight offers five modes of operation, including three modes of steady light, turbo mode and flashing Flash mode. This allows you to adjust the power of lighting to the situation and place where the flashlight is used. To facilitate the setting in the most optimal location, the Fenix ~~â€¢â€¢~~CL30R flashlight has been equipped with a thread for a tripod that we can deploy anywhere in our campsite, and a hook that allows it to be suspended on a branch or attached in a tent.

Technical parameters ~~â€¢~~ number of modes: 6 ~~â€¢~~ maximum luminous flux: 650 lm ~~â€¢~~ maximum range: 35 m ~~â€¢~~ maximum working time: 400 hours ~~â€¢~~ lifespan of the diode: up to 50,000 h ~~â€¢~~ waterproof IPX class according to IEC 529: IPX-7 / OB 4 ~~â€¢~~ housing material: anodized duralumin according to MIL-SPEC and high-quality plastic ~~â€¢~~ resistance to fall: up to 1 m ~~â€¢~~ Dual Light Beam System: yes ~~â€¢~~ Diameter: 93 mm ~~â€¢~~ height: 136 mm ~~â€¢~~ weight without batteries: 412 g ~~â€¢~~ elements of the set: flashlight, Fenix ~~â€¢â€¢~~ARB-L18 battery (18650, 2600 mAh, 3.6 V, Li-ion) x 3, microUSB cable, spare o-ring x 1 (spare gasket) Warranty 5 years