

teleskopy.pl



In the field and at competitions, when every second can decide about victory, quick aiming is necessary. The Firefield target is designed for instant and precise shooting. Ideally suited for shelling in motion. It has an additional tightness in accordance with the IPX4 standard ensuring resistance to harsh weather conditions. You can change the brightness and color of the viewfinder at any time from one of four shades of red and four shades of green. Technical parameters

- types of nets: 5 MOA dot, dotted circle - 5 MOA central dot with a circle of 45 MOA, 1 MOA cross and 40 MOA spins, 1 MOA cross with a cross, diameter wheels 30 MOA, cross 40 MOA
- brightness: from 0 to 5
- magnification: 1x
- dimensions of the window: 33 x 24 mm
- window material: glass
- field of view: 20 ° / 350 m / 1000 m
- height adjustment: 50 MOA
- supply air control: 50 MOA
- finish color: matt black
- housing material: aluminum
- maximum recoil: 600G
- resistance to difficult conditions: yes, IPX4 certificate
- resistance to smoke: yes
- shock resistance: yes
- lens cover: AR
- assembly type: Weaver
- battery type: CR2032
- operating time: from 25 hours to 180 hours depending on the mode
- battery voltage: 3 V
- operating temperature: 8 ° C to 67 ° C
- dimensions: 81 mm / 38 mm / 56 mm
- weight: 90 g
- Warranty 24 months