

teleskopy.pl



Extremely versatile Swarovski binoculars of the SLC New series are some of the most desirable high-end binoculars. The latest version of the SLC line further increases the ergonomics of use. These binoculars are suitable for virtually all applications in all conditions, are waterproof and covered by a 10-year manufacturer's warranty. Usage scenery birds hunting planes astronomy

SLCnew 8x30 WB	SLCnew 7x42 B	SLCnew 10x42 WB	SLCnew 7x50 B	SLCnew 8x50 B	SLCnew 10x50 WB	SLCnew 8x56 B	SLCnew 15x56 WB
Magnification	8x	7x	10x	7x	8x	10x	8x
Diameter of the lenses (mm)	thirty	42	42	50	50	50	56
Diameter of the lenses (inches)	1.18	1.65	1.65	1.97	1.97	1.97	2.2
Diameter of the exit pupil (mm)	3.8	6	4.2	7.1	6.3	5	7
Diameter of exit pupil (inches)	0.15	0.24	0.17	0.28	0.25	0.2	0.28
Retraction of the exit pupil (mm)	15	19	14	23	21	17	22
Retraction of the exit pupil (inches)	0.59	0.75	0.55	0.91	0.83	0.67	0.87
Actual field of view (m / 100 m)	136	140	110	124	123	112	115
Actual field of view (ft / 1000 yds)	408	420	330	372	369	336	345
Actual field of view (degree)	60	55	62	50	56	63	52
Minimum focusing distance	64	64	64	64	64	64	64

(m)	4	4	4	6	6	5	9	8	Minimum focusing distance (ft)	13	13	13	20	20	16	thirty	26	Dioptic sharpness correction							
(dpt)	+5	-3	+	+	-5	-3	+	-3	+	-2.5	+	-5	Adjusting the distance between the pupils (mm)	56-72	56-72	56-72	56-72	56-72							
	57-72	57-72	57-72	59-72	59-72	59-72	59-72	59-72	Adjusting the pupil spacing (inches)	2,2-2,83	2,2-2,83	2,2-2,83	2,2-2,83	2,24-2,83	2,24-2,83	2,24-2,83	2,24-2,83	2,24-2,83							
	2,32-2,83	2,32-2,83	2,32-2,83	2,32-2,83	2,32-2,83	2,32-2,83	2,32-2,83	2,32-2,83	Twilight efficiency (DIN 58388)	16	17	21	19	20	22	21	29	Length (mm)							
	141	164	147	200	198	196	215	215	Length (inches)	5.55	6.46	5.79	7.87	7.8	7.72	8.47	8.46	Width (mm)							
	110	122	122	126	126	126	128	128	Width (inches)	4.33	4.8	4.8	4.96	4.96	4.96	5.04	5.04	Height (mm)							
	64	71	71	69	69	69	71	71	Height (inches)	2.52	2.8	2.8	2.72	2.72	2.72	2.8	2.8	Weight (g)							
	590	950	870	1150	1150	1160	1240	1290	Weight (oz)	20.8	33.5	30.7	40.6	40.6	40.9	43.7	45.5	Colour							
	green	green	green	green	green	green	green	green	Other features / parameters	â€œ Operating temperature range: -20 to + 55 ° C								â€œ Storage temperature range: -30 to + 70 ° C							
	â€œ Water tightness: up to a depth of 4m (filled with nitrogen)																Warranty		10 years						